



MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ALL-SOLV
CS06AE

SECTION 1: PRODUCT INFORMATION

Distributed By: Bridgepoint Systems, 4282 W 590 W, Salt Lake City, Utah 84123
Company Phone Number: 801-261-1282
Emergency Phone Number: 1-800-535-5053 (Infotrac)
Date Prepared: 4/1/08 c

Hazard Rating (Zero=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme)
Fire: 4 Health: 2 Reactivity: 0

SECTION 2: INGREDIENTS

<u>PRINCIPLE HAZARDOUS INGREDIENTS :</u>	<u>TLV</u>
Toluene (CAS # 108-88-3)	100
Acetone (CAS # 67-64-1)	750
Ethylene Glycol N-Butyl Ether (CAS#111-76-2)	25
Propane (CAS # 74-98-6)	1000
Methyl Ethyl Ketone (CAS # 78-93-3)	200

SECTION 3: PHYSICAL DATA

Boiling Point (°F).....N/A	Specific
Vapor Pressure (mmHg.)..... Aerosols: Max 60	Gravity(H ₂ O=1).....Concentrate
Vapor Density (AIR=1)..... N/E	Only - .84
Solubility in Water.....Partial	Percent Volatile by Volume...N/A
	PH (1% Solution).....N/A

Appearance & Odor.....Clear Liquid, aromatic solvent odor

SECTION 4: FIRE, EXPLOSION & REACTIVITY DATA

Flash Point: 49 ° F

Extinguishing Media: Foam, dry chemical, carbon dioxide, water

Special Fire Fighting Procedures: Self contained breathing apparatus

Unusual Fire and Explosion Hazards: Do not expose aerosols to temperatures above 130°F or container may rupture

Stability: Stable

Chemical Incompatibility: Acids and strong oxidizers

Hazardous Decomposition or Byproducts: CO, CO₂

Hazardous Polymerization: Will not occur

Conditions to Avoid: Open flame, welding arcs, heat, sparks

