

## **SAFETY DATA SHEET**

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System. THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)  
IMPORTANT: Read this SDS before handling & disposing of this product.  
Pass this information on to employees, customers, & users of this product.

### **SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER**

PRODUCT IDENTITY: WHITE LIGHTNING CC09  
PRODUCT PURPOSE: CARPET EXTRACTION RINSE  
COMPANY IDENTITY: Bridgepoint Systems  
COMPANY ADDRESS: 4282 S 590 W  
COMPANY CITY: Salt Lake City, UT 84123  
COMPANY PHONE: 1-800-658-5314  
EMERGENCY PHONES: INFOTRAC: 1-800-535-5053 (USA)



### **SECTION 2. HAZARDS IDENTIFICATION**

#### **CAUTION**

#### **HAZARD STATEMENTS:**

H100s = General, H200s = Physical, H300s = Health, H400s = Environmental

- H315 Causes skin irritation.
- H320 Causes eye irritation.
- H335 May cause respiratory irritation.

#### **PRECAUTIONARY STATEMENTS:**

P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present & easy to do - Continue rinsing.

**SEE SECTIONS 8, 11 & 12 FOR TOXICOLOGICAL INFORMATION.**

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

<b>MATERIAL</b>	<b>CAS#</b>	<b>EINECS#</b>	<b>WT %</b>
Sodium Tripolyphosphate	7758-29-4	-	Trade Secret
Sodium Metasilicate	6834-92-0	-	Trade Secret
Sodium Carbonate	497-19-8	-	Trade Secret
2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	Trade Secret

TRACE COMPONENTS: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

### **SECTION 4. FIRST AID MEASURES**

#### **EYE CONTACT:**

For eyes, flush with plenty of water for 15 minutes & get medical attention.

#### **SKIN CONTACT:**

In case of contact with skin immediately remove contaminated clothing.  
Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

#### **INHALATION:**

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR).  
CALL A PHYSICIAN immediately!

COMPANY IDENTITY: Bridgepoint Systems  
 PRODUCT IDENTITY: WHITE LIGHTNING

SDS DATE: 09/03/2013  
 ORIGINAL: 09/03/2013

**SECTION 4. FIRST AID MEASURES (CONTINUED)**

SWALLOWING:

Rinse mouth. GET MEDICAL ATTENTION IMMEDIATELY. Do NOT give liquids to an unconscious or convulsing person.

**SECTION 5. FIRE FIGHTING MEASURES**

FIRE & EXPLOSION PREVENTIVE MEASURES

EXTINGUISHING MEDIA

Use dry powder, carbon dioxide. . use appropriate extinguishing media.

SPECIAL FIRE FIGHTING PROCEDURES

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots). Use NIOSH approved positive-pressure self-contained breathing apparatus.

UNUSUAL EXPLOSION AND FIRE PROCEDURES

Isolate from oxidizers, heat, & open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

PERSONAL PROTECTIVE MEASURES:

Keep unprotected personnel away. Wear appropriate personal protective equipment given in Section 8.

ENVIRONMENTAL PRECAUTIONS:

Keep from entering storm sewers and ditches which lead to waterways.

CONTAINMENT AND CLEAN-UP MEASURES:

Stop spill at source. Dike and contain. Collect leaking & spilled liquid in sealable containers as far as possible.

**SECTION 7. HANDLING AND STORAGE**

HANDLING

Use only with adequate ventilation. Avoid or repeated breathing of vapor or spray mist. Do not get in eyes, on skin or clothing. Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse.

STORAGE

Isolate from strong oxidants. Keep container tightly closed & upright when not in use to prevent leakage.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

MATERIAL	CAS#	EINECS#	TWA (OSHA)	TLV (ACGIH)
Sodium Tripolyphosphate	7758-29-4	-	None Known	None Known
Sodium Metasilicate	6834-92-0	-	None Known	None Known
Sodium Carbonate	497-19-8	-	None Known	None Known
2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	None Known	25 ppm

MATERIAL	CAS#	EINECS#	CEILING	STEL(OSHA/ACGIH)	HAP
2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	None Known	None Known	Yes

Each component showing `Yes' under "HAP" is an EPA Hazardous Air Pollutant.

COMPANY IDENTITY: Bridgepoint Systems  
 PRODUCT IDENTITY: WHITE LIGHTNING

SDS DATE: 09/03/2013  
 ORIGINAL: 09/03/2013

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION (CONTINUED)**

#### RESPIRATORY EXPOSURE CONTROLS

A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z86.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

#### VENTILATION

LOCAL EXHAUST: Necessary                      MECHANICAL (GENERAL): Acceptable  
 SPECIAL: None                                      OTHER: None  
 Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

#### PERSONAL PROTECTIONS:

Wear OSHA Standard goggles & gloves as a standard practice.

### **SECTION 9. PHYSICAL & CHEMICAL PROPERTIES**

APPEARANCE:	Powder, Opaque, White
ODOR:	Mild floral
ODOR THRESHOLD:	Not Available
pH (Neutrality):	11.2 (1.0%)
MELTING POINT/FREEZING POINT:	Not Available
BOILING RANGE (IBP,50%,Dry Point):	Not Applicable
FLASH POINT (TEST METHOD):	Not Applicable
EVAPORATION RATE (n-BUTYL ACETATE=1):	Not Applicable
FLAMMABILITY CLASSIFICATION:	Class
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	1.1
UPPER FLAMMABLE LIMIT IN AIR (% by vol):	Not Available
VAPOR PRESSURE (mm of Hg)@20 C	0.07
VAPOR DENSITY (air=1):	Not Applicable
GRAVITY @ 68/68F / 20/20C:	
BULK DENSITY:	0.638 g/cc
POUNDS/GALLON:	Not Available
WATER SOLUBILITY:	Complete
PARTITION COEFFICIENT (n-Octane/Water):	Not Available
AUTO IGNITION TEMPERATURE:	Not Applicable
DECOMPOSITION TEMPERATURE:	Not Available

### **SECTION 10. STABILITY & REACTIVITY**

#### STABILITY

Stable under normal conditions.

#### CONDITIONS TO AVOID

Isolate from oxidizers, heat, & open flame.

#### MATERIALS TO AVOID

Reacts with strong oxidants, causing fire & explosion hazard.

#### HAZARDOUS DECOMPOSITION PRODUCTS

Carbon Monoxide, Carbon Dioxide, Phosphorus Pentoxide, Sodium Oxide & Hydroxide, Silicon Dioxide, Sulfur Oxide from extreme heating.

#### HAZARDOUS POLYMERIZATION

Will not occur.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### ACUTE HAZARDS

#### EYE & SKIN CONTACT:

Primary irritation to skin, defatting, dermatitis.  
 Absorption thru skin increases exposure.

COMPANY IDENTITY: Bridgepoint Systems  
 PRODUCT IDENTITY: WHITE LIGHTNING

SDS DATE: 09/03/2013  
 ORIGINAL: 09/03/2013

## **SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)**

Primary irritation to eyes, redness, tearing, blurred vision.  
 Powder can cause eye irritation. Wash thoroughly after handling.

### **INHALATION:**

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.

### **SWALLOWING:**

Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

### **SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED**

#### **CONDITIONS AGGRAVATED**

Persons with severe skin, liver or kidney problems should avoid use.

### **CHRONIC HAZARDS**

#### **CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:**

This product has no carcinogens listed by IARC, NTP, NIOSH, OSHA or ACGIH, as of this date, greater or equal to 0.1%.  
 Absorption thru skin may be harmful.

**IRRITANCY OF PRODUCT:** This product is irritating to contaminated tissue.  
**SENSITIZATION TO THE PRODUCT:** No component of this product is known to be a sensitizer.  
**MUTAGENICITY:** This product is not reported to produce mutagenic effects in humans.  
**EMBRYOTOXICITY:** This product is not reported to produce embryotoxic effects in humans.  
**TERATOGENICITY:** This product is not reported to produce teratogenic effects in humans.  
**REPRODUCTIVE TOXICITY:** This product is not reported to cause reproductive effects in humans.

A mutagen is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An embryotoxin is a chemical which causes damage to a developing embryo (such as: within the eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A teratogen is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A reproductive toxin is any substance which interferes in any way with the reproductive process.

### **MAMMALIAN TOXICITY INFORMATION**

<b>MATERIAL</b>	<b>CAS#</b>	<b>EINECS#</b>	<b>LOWEST KNOWN LETHAL DOSE DATA</b>
Diethylene Glycol Butyl Ether	112-34-5	-	LOWEST KNOWN LD50 (ORAL) 6560.0 mg/kg (Rats)
Diethylene Glycol Butyl Ether	112-34-5	-	LOWEST KNOWN LD50 (SKIN) 4120.0 mg/kg (Rabbits)

## **SECTION 12. ECOLOGICAL INFORMATION**

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

### **EFFECT OF MATERIAL ON PLANTS AND ANIMALS:**

This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's components on test animals.

### **EFFECT OF MATERIAL ON AQUATIC LIFE:**

No aquatic environmental information is available on this product.

### **MOBILITY IN SOIL**

Mobility of this material has not been determined.

### **DEGRADABILITY**

This product is completely biodegradable.

### **ACCUMULATION**

Bioaccumulation of this product has not been determined.

COMPANY IDENTITY: Bridgepoint Systems  
 PRODUCT IDENTITY: WHITE LIGHTNING

SDS DATE: 09/03/2013  
 ORIGINAL: 09/03/2013

### SECTION 13. DISPOSAL CONSIDERATIONS

Processing, use or contamination may change the waste disposal requirements. Do not dispose of on land, in surface waters, or in storm drains. Waste should be recycled or disposed of in accordance with regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal.

**ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES.**

### SECTION 14. TRANSPORT INFORMATION

DOT/TDG SHIP NAME: Not Regulated  
 DRUM LABEL: None  
 IATA / ICAO: Not Regulated  
 IMO / IMDG: Not Regulated  
 EMERGENCY RESPONSE GUIDEBOOK NUMBER: None

### SECTION 15. REGULATORY INFORMATION

EPA REGULATION:  
 SARA SECTION 311/312 HAZARDS: Acute Health



All components of this product are on the TSCA list.

SARA Title III Section 313 Supplier Notification

This product contains the indicated <\*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

SARA TITLE III INGREDIENTS	CAS#	EINECS#	WT%	(REG. SECTION)	RQ(LBS)
*2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	0-10	(313)	None

Any release equal to or exceeding the RQ must be reported to the National Response Center (800-424-8802) and appropriate state and local regulatory agencies as described in 40 CFR 302.6 and 40 CFR 355.40 respectively. Failure to report may result in substantial civil and criminal penalties. State & local regulations may be more restrictive than federal regulations.

#### STATE REGULATIONS:

CALIFORNIA SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT (PROPOSITION 65):  
 This product contains no chemicals known to the State of California to cause cancer or reproductive toxicity.

#### INTERNATIONAL REGULATIONS

The components of this product are listed on the chemical inventories of the following countries:  
 Australia (AICS), Canada (DSL or NDSL), China (IECSC), Europe (EINECS, ELINCS)G  
 Japan (METI/CSCL, MHLW/ISHL), South Korea (KECI), New Zealand (NZIoC),  
 Philippines (PICCS), Switzerland (SWISS), Taiwan (NECSI), USA (TSCA).

CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)  
 D2B: Irritating to skin / eyes.

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

### SECTION 16. OTHER INFORMATION

#### HAZARD RATINGS:

HEALTH (NFPA): 1, HEALTH (HMIS): 1, FLAMMABILITY: 0, PHYSICAL HAZARD: 0  
 (Personal Protection Rating to be supplied by user based on use conditions.)

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

COMPANY IDENTITY: Bridgepoint Systems  
PRODUCT IDENTITY: WHITE LIGHTNING

SDS DATE: 09/03/2013  
ORIGINAL: 09/03/2013

**SECTION 16. OTHER INFORMATION (CONTINUED)**

**EMPLOYEE TRAINING**

See Section 2 for Risk & Safety Statements. Employees should be made aware of all hazards of this material (as stated in this SDS) before handling it.

SDS DATE: 09/03/2013

**NOTICE**

Bridgepoint Systems disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.