

SAFETY DATA SHEET

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System.

THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)

IMPORTANT: Read this SDS before handling & disposing of this product.

Pass this information on to employees, customers, & users of this product.

SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

PRODUCT IDENTITY: FLEX CC22
PRODUCT PURPOSE: CARPET PRE-SPRAY
COMPANY IDENTITY: Bridgepoint Systems
COMPANY ADDRESS: 4282 S 590 W
COMPANY CITY: Salt Lake City, UT 84123
COMPANY PHONE: 1-800-658-5314
EMERGENCY PHONES: INFOTRAC: 1-800-535-5053 (USA)

SECTION 2. HAZARDS IDENTIFICATION

DANGER!!



HAZARD STATEMENTS:

H100s = General, H200s = Physical, H300s = Health, H400s = Environmental

H302 Harmful if swallowed.
H315 Causes skin irritation.
H320 Causes eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H371 May cause damage to organs.

PRECAUTIONARY STATEMENTS:

P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal

P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P264 Wash with soap & water thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+352 IF ON SKIN: Wash with soap & water.
P304+340 IF INHALED: Remove victim to fresh air & keep at rest in a position comfortable for breathing.
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present & easy to do - Continue rinsing.
P309+311 If exposed or you feel unwell: Call a POISON CENTER or doctor/physician.
P332+313 If skin irritation occurs: Get medical advice/attention.
P337+313 If eye irritation persists, get medical advice/attention.

SEE SECTIONS 8, 11 & 12 FOR TOXICOLOGICAL INFORMATION.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MATERIAL	CAS#	EINECS#	WT %
Sodium Metasilicate Pentahydrate	6834-92-0	-	Trade Secret
Sodium Tripolyphosphate	7758-29-4	-	Trade Secret
2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	Trade Secret
2-Butoxyethanol	111-76-2	203-905-0	Trade Secret
Potassium Pyrophosphate	7320-34-5	-	Trade Secret

TRACE COMPONENTS: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

COMPANY IDENTITY: Bridgepoint Systems
PRODUCT IDENTITY: FLEX

SDS DATE: 02/10/2014
ORIGINAL: 02/10/2014

SECTION 4. FIRST AID MEASURES

GENERAL ADVICE:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists, refer to Section 8 for specific personal protective equipment.

EYE CONTACT:

If this product enters the eyes, open eyes while under gently running water. Use sufficient force to open eyelids. "Roll" eyes to expose more surface. Minimum flushing is for 15 minutes. Seek immediate medical attention.

SKIN CONTACT:

If the product contaminates the skin, immediately begin decontamination with running water. Minimum flushing is for 15 minutes. Remove contaminated clothing, taking care not to contaminate eyes. If skin becomes irritated and irritation persists, medical attention may be necessary. Wash contaminated clothing before reuse, discard contaminated shoes.

INHALATION:

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR). Seek immediate medical attention.

SWALLOWING:

If swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, give two glasses of water to drink. DO NOT INDUCE VOMITING. Never induce vomiting or give liquids to someone who is unconscious, having convulsions, or unable to swallow. Seek immediate medical attention.

NOTES TO PHYSICIAN:

There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Any material aspirated during vomiting may cause lung injury. Therefore, emesis should not be induced mechanically or pharmacologically. If it is considered necessary to evacuate the stomach contents, this should be done by means least likely to cause aspiration (such as: Gastric lavage after endotracheal intubation).

SECTION 5. FIRE FIGHTING MEASURES

FIRE & EXPLOSION PREVENTIVE MEASURES

Above flash point, use a closed system, ventilation,

EXTINGUISHING MEDIA

Use dry powder, alcohol-resistant foam, water spray, carbon dioxide. .
use appropriate extinguishing media.

SPECIAL FIRE FIGHTING PROCEDURES

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used.
Do not enter confined fire-space without full bunker gear.
(Helmet with face shield, bunker coats, gloves & rubber boots).

UNUSUAL EXPLOSION AND FIRE PROCEDURES

Isolate from oxidizers, heat, & open flame.
Closed containers may explode if exposed to extreme heat.
Applying to hot surfaces requires special precautions.

SECTION 6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE AND ENVIRONMENTAL PRECAUTIONS:

Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. In case of a spill, clear the affected area, protect people, and respond with trained personnel. ELIMINATE all ignition sources (no smoking, flares, sparks, or flames in immediate area).

COMPANY IDENTITY: Bridgepoint Systems
 PRODUCT IDENTITY: FLEX

SDS DATE: 02/10/2014
 ORIGINAL: 02/10/2014

SECTION 6. ACCIDENTAL RELEASE MEASURES (CONTINUED)

PERSONAL PROTECTIVE EQUIPMENT

The proper personal protective equipment for incidental releases (such as: 1 Liter of the product released in a well-ventilated area), use impermeable gloves, they should be Level B: triple-gloves (rubber gloves and nitrile gloves over latex gloves), chemical resistant suit and boots, hard-hat, and Self-Contained Breathing Apparatus specific for the material handled, goggles, face shield, and appropriate body protection. In the event of a large release, use impermeable gloves, specific for the material handled, chemically resistant suit and boots, and hard hat. Self-Contained Breathing Apparatus or respirator may be required where engineering controls are not adequate or conditions for potential exposure exist. When respirators are required, select NIOSH/MSHA approved based on actual or potential airborne concentrations in accordance with latest OSHA and/or ANSI recommendations.

ENVIRONMENTAL PRECAUTIONS:

Stop spill at source. Construct temporary dikes of dirt, sand, or any appropriate readily available material to prevent spreading of the material. Close or cap valves and/or block or plug hole in leaking container and transfer to another container. Keep from entering storm sewers and ditches which lead to waterways, and if necessary, call the local fire or police department for immediate emergency assistance.

CONTAINMENT AND CLEAN-UP MEASURES:

Absorb spilled liquid with polypads or other suitable absorbent materials. If necessary, neutralize using suitable buffering material, (acid with soda ash or base with phosphoric acid), and test area with litmus paper to confirm neutralization. Clean up with non-combustible absorbent (such as: sand, soil, and so on). Shovel up and place all spill residue in suitable containers. dispose of at an appropriate waste disposal facility according to current applicable laws and regulations and product characteristics at time of disposal (see Section 13 - Disposal Considerations).

SECTION 7. HANDLING AND STORAGE

HANDLING

Use only with adequate ventilation. Avoid or repeated breathing of vapor or spray mist. Do not get in eyes, on skin or clothing. Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse.

STORAGE

Isolate from strong oxidants. Do not store above 49 C/120 F.
 Keep container tightly closed & upright when not in use to prevent leakage.

NONBULK: CONTAINERS:

Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Material should be stored in secondary containers or in a diked area, as appropriate. Store containers away from incompatible chemicals (see Section 10, Stability and Reactivity). Post warning and "NO SMOKING" signs in storage and use areas, as appropriate. Empty containers should be handled with care. Never store food, feed, or drinking water in containers which held this product.

EMPTY CONTAINER WARNING:

Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

MATERIAL	CAS#	EINECS#	TWA (OSHA)	TLV (ACGIH)
Sodium Metasilicate Pentahydrate	6834-92-0	-	None Known	None Known
Sodium Tripolyphosphate	7758-29-4	-	None Known	None Known
2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	None Known	25 ppm
2-Butoxyethanol	111-76-2	203-905-0	50 ppm S	20 ppm S
Potassium Pyrophosphate	7320-34-5	-	None Known	None Known

COMPANY IDENTITY: Bridgepoint Systems
 PRODUCT IDENTITY: FLEX

SDS DATE: 02/10/2014
 ORIGINAL: 02/10/2014

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION (CONTINUED)

MATERIAL	CAS#	EINECS#	CEILING	STEL(OSHA/ACGIH)	HAP
2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	None Known	None Known	Yes

Each component showing `Yes' under "HAP" is an EPA Hazardous Air Pollutant.

RESPIRATORY EXPOSURE CONTROLS

Maintain airborne contaminant concentrations below exposure limits given above. If respiratory protection is needed, use only protection authorized in 29 CFR 1910.134, European Standard EN 149, or applicable State regulations. If adequate ventilation is not available or there is potential for airborne exposure above the exposure limits, a respirator may be worn up to the respirator exposure limitations, check with respirator equipment manufacturer's recommendations/limitations. For a higher level of protection, use positive pressure supplied air respiration protection or Self-Contained Breathing Apparatus or if oxygen levels are below 19.5% or are unknown.

VENTILATION

LOCAL EXHAUST:	Necessary	MECHANICAL (GENERAL):	Necessary
SPECIAL:	None	OTHER:	None

Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

EYE PROTECTION:

Splash goggles or safety glasses. Face-shields are recommended when the operation can generate splashes, sprays or mists.

HAND PROTECTION:

Use gloves chemically resistant to this material. Preferred examples: Butyl rubber, Chlorinated Polyethylene, Polyethylene, Ethyl Vinyl Alcohol Laminate ("EVAL"), Polyvinyl Alcohol ("PVA"). Examples of acceptable glove barrier materials include: Natural Rubber ("Latex"), Neoprene, Nitrile/Butadiene Rubber ("Nitril") or ("NBR"), Polyvinyl Chloride ("PVC" or "Vinyl"), Viton.

BODY PROTECTION:

Use body protection appropriate for task.

SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE:	Clear Liquid
ODOR:	Lemon
ODOR THRESHOLD:	Not Available
pH (Neutrality):	12.4
MELTING POINT/FREEZING POINT:	Not Available
BOILING RANGE (IBP,50%,Dry Point):	100 100 235* C/212 212 455* F(*=End Point)
FLASH POINT (TEST METHOD):	> 93 C / > 201 F
EVAPORATION RATE (n-Butyl Acetate=1):	Not Applicable
FLAMMABILITY CLASSIFICATION:	Class IIIA
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	Not Applicable
UPPER FLAMMABLE LIMIT IN AIR (% by vol):	Not Available
VAPOR PRESSURE (mm of Hg)@20 C	17.5
VAPOR DENSITY (air=1):	0.688
GRAVITY @ 68/68 F / 20/20 C:	
DENSITY:	1.046
SPECIFIC GRAVITY (Water=1):	1.047
POUNDS/GALLON:	8.729
WATER SOLUBILITY:	Complete
PARTITION COEFFICIENT (n-Octane/Water):	Not Available
AUTO IGNITION TEMPERATURE:	Not Applicable
DECOMPOSITION TEMPERATURE:	Not Available
VOCs (>0.044 Lbs/Sq In) :	Not Available
TOTAL VOC'S (TVOC)*:	0.13 Lbs/Gal
NONEXEMPT VOC'S (CVOC)*:	0.13 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS):	1.4 Wt%
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C)	Not
VISCOSITY @ 20 C (ASTM D445):	Not Available

* Using CARB (California Air Resources Board Rules).

COMPANY IDENTITY: Bridgepoint Systems
PRODUCT IDENTITY: FLEX

SDS DATE: 02/10/2014
ORIGINAL: 02/10/2014

SECTION 10. STABILITY & REACTIVITY

STABILITY

Stable under normal conditions.

CONDITIONS TO AVOID

Isolate from oxidizers, heat, & open flame.

MATERIALS TO AVOID

Reacts with strong oxidants, causing fire & explosion hazard.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon Monoxide, Carbon Dioxide, Sodium Oxide & Hydroxide, Sulfur Oxides from heating.

HAZARDOUS POLYMERIZATION

Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

ACUTE HAZARDS

EYE & SKIN CONTACT:

Primary irritation to skin, defatting, dermatitis.
Absorption thru skin increases exposure.
Primary irritation to eyes, redness, tearing, blurred vision.
Liquid can cause eye irritation. Wash thoroughly after handling.

INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful. Breathing vapor can cause irritation. Acute overexposure can cause harm to affected organs by routes of entry.

SWALLOWING:

Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED

CONDITIONS AGGRAVATED

Chronic overexposure can cause harm to affected organs by routes of entry. Persons with severe skin, liver or kidney problems should avoid use.

CHRONIC HAZARDS

CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:

This product has no carcinogens listed by IARC, NTP, NIOSH, OSHA or ACGIH, as of this date, greater or equal to 0.1%. Absorption thru skin may be harmful.

IRRITANCY OF PRODUCT: This product is irritating to contaminated tissue.

SENSITIZATION TO THE PRODUCT: No component of this product is known as a sensitizer.

MUTAGENICITY: No known reports of mutagenic effects in humans.

EMBRYOTOXICITY: No known reports of embryotoxic effects in humans.

TERATOGENICITY: No known reports of teratogenic effects in humans.

REPRODUCTIVE TOXICITY: No known reports of reproductive effects in humans.

A mutagen is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An embryotoxin is a chemical which causes damage to a developing embryo (such as: within the eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A teratogen is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A reproductive toxin is any substance which interferes in any way with the reproductive process.

COMPANY IDENTITY: Bridgepoint Systems
 PRODUCT IDENTITY: FLEX

SDS DATE: 02/10/2014
 ORIGINAL: 02/10/2014

SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)

MAMMALIAN TOXICITY INFORMATION

MATERIAL	CAS#	EINECS#	LOWEST KNOWN LETHAL DOSE DATA
Ethylene Glycol Butyl Ether	111-76-2	-	LOWEST KNOWN LD50 (ORAL) 320.0 mg/kg(Rabbits)
Ethylene Glycol Butyl Ether	111-76-2	-	LOWEST KNOWN LC50 (VAPORS) 700 ppm (Mice)
Ethylene Glycol Butyl Ether	111-76-2	-	LOWEST KNOWN LD50 (SKIN) 440.0 mg/kg (Rabbits)

SECTION 12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

EFFECT OF MATERIAL ON PLANTS AND ANIMALS:

This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's components on test animals.

EFFECT OF MATERIAL ON AQUATIC LIFE:

The most sensitive known aquatic group to any component of this product is: Tidewater Silversides 1250 ppm or mg/L (96 hour exposure).
 Keep out of sewers and natural water supplies.

MOBILITY IN SOIL

Mobility of this material has not been determined.

DEGRADABILITY

This product is partially biodegradable.

ACCUMULATION

Bioaccumulation of this product has not been determined.

SECTION 13. DISPOSAL CONSIDERATIONS

Processing, use or contamination may change the waste disposal requirements. Do not dispose of on land, in surface waters, or in storm drains. Waste should be recycled or disposed of in accordance with regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal.
ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES.

SECTION 14. TRANSPORT INFORMATION

MARINE POLLUTANT: No
 DOT/TDG SHIP NAME: Not Regulated
 DRUM LABEL: None
 IATA / ICAO: Not Regulated
 IMO / IMDG: Not Regulated
 EMERGENCY RESPONSE GUIDEBOOK NUMBER: None

SECTION 15. REGULATORY INFORMATION

EPA REGULATION:

SARA SECTION 311/312 HAZARDS: Acute Health
 All components of this product are on the TSCA list.

SARA Title III Section 313 Supplier Notification

This product contains the indicated <*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

SARA TITLE III INGREDIENTS	CAS#	EINECS#	WT%	(REG.SECTION)	RQ(LBS)
*2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	0- 5	(313)	None
*2-Butoxyethanol	111-76-2	203-905-0	0- 5	(313)	None



COMPANY IDENTITY: Bridgepoint Systems
PRODUCT IDENTITY: FLEX

SDS DATE: 02/10/2014
ORIGINAL: 02/10/2014

SECTION 15. REGULATORY INFORMATION (CONTINUED)

STATE REGULATIONS:

THIS PRODUCT MEETS REQUIREMENTS OF SOUTHERN
CALIFORNIA AQMD RULE 443.1 & SIMILAR REGULATIONS

CALIFORNIA SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT (PROPOSITION 65):

This product contains no chemicals known to the State of California
to cause cancer or reproductive toxicity.

INTERNATIONAL REGULATIONS

The identified components of this product are listed on the chemical inventories
of the following countries:

Australia (AICS), Canada (DSL or NDSL), China (IECSC), Europe (EINECS, ELINCS),
Japan (METI/CSCL, MHLW/ISHL), South Korea (KECI), New Zealand (NZIoC),
Philippines (PICCS), Switzerland (SWISS), Taiwan (NECSI), USA (TSCA).

CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

D2B: Irritating to skin / eyes.

This product has been classified in accordance with hazard criteria of the Controlled
Products Regulations (CPR) and the SDS contains all information required by the CPR.

SECTION 16. OTHER INFORMATION

HAZARD RATINGS:

HEALTH (NFPA): 1, HEALTH (HMIS): 1, FLAMMABILITY: 1, PHYSICAL HAZARD: 0
(Personal Protection Rating to be supplied by user based on use conditions.)

This information is intended solely for the use of individuals
trained in the NFPA & HMIS hazard rating systems.

EMPLOYEE TRAINING

See Section 2 for Risk & Safety Statements. Employees should be made aware
of all hazards of this material (as stated in this SDS) before handling it.

SDS DATE: 02/10/2014

NOTICE

Bridgepoint Systems disclaims all expressed or implied warranties of merchantability or
fitness for a specific use, with respect to the product or the information provided herein,
except for conformation to contracted specifications. All information appearing herein
is based upon data obtained from manufacturers and/or recognized technical sources.
While the information is believed to be accurate, we make no representations as to its
accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible for
verifying the data under their own operating conditions to determine whether the product
is suitable for their particular purposes and they assume all risks of their handling,
and disposal of the product. Users also assume all risks in regards to the publication
or use of, or reliance upon information contained herein.

This information relates only to the product designated herein, and does not relate to
its use in combination with any other material or process.