

Power Strike

MSDS Number: S787

Revision Date: November 14, 2013

Page 1 of 5

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Kärcher North America, Inc.
Prochem
325 S. Price Road
Chandler, AZ 85224

Contact: Prochem
Phone: 480-899-7000
Fax: 480-786-9538
Email: info@prochem.com
Web: www.prochem.com

Product Name: Power Strike
Revision Date: November 14, 2013
Version: 46-5A
MSDS Number: S787

Emergency Information: INFOTRAC 1-800-535-5053 International 1-352-323-3500

2 HAZARDS IDENTIFICATION

- Route of Entry:** Eyes; Skin; Inhalation;
Target Organs: Eyes; Skin;
Inhalation: Minimal respiratory tract irritation may occur with exposure to a large amount of material.
Skin Contact: May cause irritation.
Eye Contact: May cause irritation.
Ingestion: Ingestion is not applicable route of entry for intended use.

NFPA:
HMIS III:

Health = 2, Fire = 1, Reactivity = 0
H2/F1/PH0



HMIS III	
HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARDS	0
PERSONAL PROTECTION B Safety Glasses, Gloves	

PERSONAL PROTECTION INDEX													
A	👁️		G	👁️ + 🧤 + 🦺	B	👁️ + 🧤	H	👁️ + 🧤 + 🦺 + 🦾	C	👁️ + 🧤 + 🦺	I	👁️ + 🧤 + 🦺	
D	👁️ + 🧤 + 🦺	J	👁️ + 🧤 + 🦺 + 🦾	E	👁️ + 🧤 + 🦺	K	👁️ + 🧤 + 🦺 + 🦾 + 🦷	F	👁️ + 🧤 + 🦺 + 🦾	X	Consult your supervisor or S.O.P. for "SPECIAL" handling directions		
A	🦺	n	👁️	o	👁️	p	🧤	q	🦺	r	🦺	s	🦺
t	🦺	u	🦺	w	🦺	y	🦺	z	🦺	Additional Information			
<small> Safety Glasses Splash Goggles Face Shield & Eye Protection Gloves Boots Synthetic Apron Full Suit Dust Respirator Vapor Respirator Dust & Vapor Respirator Full Face Respirator Airline Hood or Mask </small>													

GHS Classifications:

- Health, Acute toxicity, 5 Oral
- Health, Skin corrosion/irritation, 3
- Health, Serious Eye Damage/Eye Irritation, 2 B

Power Strike

MSDS Number: S787

Revision Date: November 14, 2013

Page 2 of 5

GHS Phrases:

- Warning, H303 - May be harmful if swallowed
- Warning, H316 - Causes mild skin irritation
- Warning, H320 - Causes eye irritation

GHS Precautionary Statements:

- Wash thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.
- IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do.

Continue rinsing.

- Call a POISON CENTER or doctor/physician if you feel unwell.
- If eye irritation persists: Get medical advice/attention.

GHS PICTOGRAMS: No GHS Pictograms

3 HAZARDS IDENTIFICATION

Ingredients:

CAS #	Percentage	Chemical Name
111-76-2	<8%	Ethylene glycol monobutyl ether
497-19-8	<17%	Sodium Carbonate
6834-92-0	<6%	Sodium metasilicate

OSHA Regulatory Status:

This SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

4 FIRST AID MEASURES

- Inhalation:** If symptoms develop, move victim to fresh air; if symptoms persist, obtain medical attention.
- Skin Contact:** Wash with soap and water. If irritation persists consult medical personnel.
- Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Get immediate medical attention.
- Ingestion:** If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured party is conscious, give two glasses of water. Seek medical attention.

5 FIRE FIGHTING MEASURES

Flash Point: N/A

Wear self-contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

6 ACCIDENTAL RELEASE MEASURES

Keep away from drains and ground water. Keep all unnecessary personnel away. Spill area may be slippery. Sweep up, place in bag and hold for waste disposal. Ventilate area and wash spill site after material pickup is complete. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

Power Strike

MSDS Number: S787

Revision Date: November 14, 2013

Page 3 of 5

7 HANDLING AND STORAGE

Handling Precautions: Avoid contact with eyes, skin, or clothing; Consider normal working hygiene. Handle with care and avoid spillage on the floor (slippage). Keep away from sources of ignition; wash thoroughly after handling.

Storage Requirements: Store out of reach of children; keep container closed; store in a cool well-ventilated place away from strong oxidizing or alkaline product.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Normal room ventilation is satisfactory for limited use.

Personal Protective Equip: HMIS PP, B | Safety glasses, Gloves

Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Ethylene glycol butyl ether 111-76-2 OSHA PEL 50 ppm - 240 mg/m3

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White	Odor:	Floral
Physical State:	Powder	Solubility:	Soluble
Spec Grav./Density:	N/A		
pH:	10.90 @ 1% Solution/ 10.5 - 11.5 RTU		

10 STABILITY AND REACTIVITY

Stability: Product is stable under normal conditions.

Conditions to Avoid: None Known

Materials to Avoid: None Known

Hazardous Decomposition: Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified thermal decomposition products from this product or its packaging.

Hazardous Polymerization: Will not occur.

11 TOXICOLOGICAL INFORMATION

Toxicity Data:

Ethylene glycol butyl ether 111-76-2

Oral (LD 50): 917 mg/kg - Rat

Inhalation (LC 50): 2900 mg/m3/7H - Rat

Skin irritation: Mild

Eye irritation: Mild

Sensitisation: Not considered an occupational sensitizer

Power Strike

MSDS Number: S787

Revision Date: November 14, 2013

Page 4 of 5

Sodium Carbonate 497-19-8

Oral (LD 50): 4090 mg/kg - Rat

Inhalation (LC 50): 2300 mg/m³/2H - Rat

Skin irritation: Mild - Rabbit

Eye irritation: Moderate - Rabbit

Sensitization: Not considered an occupational sensitizer

Sodium Metasilicate 6834-92-0

Oral (LD 50): 1153 mg/kg - Rat

Inhalation (LC 50): Not listed on RTECS

Skin irritation: Severe

Eye irritation: Severe

Sensitization: Not considered an occupational sensitizer

12 ECOLOGICAL INFORMATION

On the basis of available information, this material is not expected to produce any significant environmental effects when recommended use instructions are followed.

13 DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.

14 TRANSPORT INFORMATION

Ship in accordance with 49 CFR parts 100-185. Non-hazardous for air, sea and road freight.

15 REGULATORY INFORMATION

COMPONENT / (CAS/PERCENT) / CODES

*Ethylene glycol monobutyl ether (111762 <8%) MASS, OSHAWAC, PA, TSCA, TXAIR, WHMIS

*Sodium Carbonate (497198 <17%) TSCA, WHMIS

*Sodium metasilicate (6834920 <6%) TSCA, WHMIS

REGULATORY KEY DESCRIPTIONS

All components are listed on TSCA

Power Strike

MSDS Number: S787

Revision Date: November 14, 2013

Page 5 of 5

MASS = MA Massachusetts Hazardous Substances List
OSHA WAC = OSHA workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level
WHMIS = Workplace Haz Mat Info Sys Canada

16

OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager

Phone Number: [480] 899-7000