

## Power Burst

MSDS Number: S789

Revision Date: November 12, 2013

Page 1 of 5

## 1 PRODUCT AND COMPANY IDENTIFICATION

### Manufacturer

Kärcher North America, Inc.  
Prochem  
325 S. Price Road  
Chandler, AZ 85224

**Contact:** Prochem  
**Phone:** 480-899-7000  
**Fax:** 480-786-9538  
**Email:** info@prochem.com  
**Web:** www.prochem.com

**Product Name:** Power Burst  
**Revision Date:** November 12, 2013  
**Version:** 44-43O  
**MSDS Number:** S789


**Emergency Information: INFOTRAC 1-800-535-5053 International 1-352-323-3500**

## 2 HAZARDS IDENTIFICATION

**Route of Entry:** Eyes; Skin; Inhalation;  
**Target Organs:** Eyes; Skin;  
**Inhalation:** Minimal respiratory tract irritation may occur with exposure to a large amount of material.  
**Skin Contact:** May cause irritation.  
**Eye Contact:** May cause irritation.  
**Ingestion:** Ingestion is not applicable route of entry for intended use.

NFPA:  
HMIS III:

Health = 2, Fire = 1, Reactivity = 0  
H2/F1/PH0



HMIS III	
HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARDS	0
PERSONAL PROTECTION B   Safety Glasses, Gloves	

PERSONAL PROTECTION INDEX			
A		G	
B		H	
C		I	
D		J	
E		K	
F		X	Consult your supervisor or S.O.P. for "SPECIAL" handling directions
A	n	o	p
 Safety Glasses	 Splash Goggles	 Face Shield & Eye Protection	 Gloves
 Dust Respirator	 Vapor Respirator	 Dust & Vapor Respirator	 Full Face Respirator
 Airline Hood or Mask	 Synthetic Apron	 Full Suit	 Additional Information

GHS Classifications:  
Health, Acute toxicity, 5 Dermal

GHS Phrases:

## Power Burst

MSDS Number: S789

Revision Date: November 12, 2013

Page 2 of 5

Warning, H313 - May be harmful in contact with skin

**GHS Precautionary Statements:**

IF ON SKIN: Wash with soap and water.

Call a POISON CENTER or doctor/physician if you feel unwell.

**GHS PICTOGRAMS:**

No GHS Pictograms

### 3 HAZARDS IDENTIFICATION

**Ingredients:**

CAS #	Percentage	Chemical Name
497-19-8	<19%	Sodium Carbonate
6834-92-0	<8%	Sodium metasilicate
7601-54-9	<6%	Sodium phosphate, tribasic
111-76-2	<4%	Ethylene Glycol Butyl Ether

**OSHA Regulatory Status:**

This SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

### 4 FIRST AID MEASURES

- Inhalation:** If symptoms develop, move victim to fresh air; if symptoms persist, obtain medical attention.
- Skin Contact:** Wash with soap and water. If irritation persists consult medical personnel.
- Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Get immediate medical attention.
- Ingestion:** If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured party is conscious, give two glasses of water. Seek medical attention.

### 5 FIRE FIGHTING MEASURES

**Flash Point:** Not Flammable

Wear self-contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

### 6 ACCIDENTAL RELEASE MEASURES

Keep away from drains and ground water. Keep all unnecessary personnel away. Spill area may be slippery. Sweep up, place in bag and hold for waste disposal. Ventilate area and wash spill site after material pickup is complete. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

## Power Burst

MSDS Number: S789

Revision Date: November 12, 2013

Page 3 of 5

### 7 HANDLING AND STORAGE

**Handling Precautions:** Avoid contact with eyes, skin, or clothing; Consider normal working hygiene. Handle with care and avoid spillage on the floor (slippage). Keep away from sources of ignition; wash thoroughly after handling.

**Storage Requirements:** Store out of reach of children; keep container closed; store in a cool well-ventilated place away from strong oxidizing or acid product.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** Normal room ventilation is satisfactory for limited use.

**Personal Protective Equip:** HMIS PP, B | Safety glasses, Gloves

Ethylene glycol butyl ether 111-76-2 OSHA PEL 50 ppm - 240 mg/m3

### 9 PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Moist white	<b>Odor:</b>	Herbal
<b>Physical State:</b>	Powder	<b>Solubility:</b>	Soluble
<b>pH:</b>	11.3 - 11.6 RTU		

### 10 STABILITY AND REACTIVITY

**Stability:** Product is stable under normal conditions.

**Conditions to Avoid:** None Known

**Materials to Avoid:** None Known

**Hazardous Decomposition:** Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified thermal decomposition products from this product or its packaging.

**Hazardous Polymerization:** Will not occur.

### 11 TOXICOLOGICAL INFORMATION

**Toxicity Data:**

Sodium Carbonate 497-19-8

Oral ( LD 50): 4090 mg/kg - Rat

Inhalation ( LC 50): 2300 mg/m3/2H - Rat

Skin irritation: Mild - Rabbit

Eye irritation: Moderate - Rabbit

Sensitization: Not considered an occupational sensitizer

Sodium Metasilicate 6834-92-0

Oral ( LD 50): 1153 mg/kg - Rat

Inhalation ( LC 50): Not listed on RTECS

## Power Burst

MSDS Number: S789

Revision Date: November 12, 2013

Page 4 of 5

Skin irritation: Severe

Eye irritation: Severe

Sensitation: Not considered an occupational sensitizer

Sodium Phosphate Tribasic 7601-54-9

Oral ( LD 50): No information on RTECS

Inhalation ( LC 50): No information on RTECS

Skin irritation: Moderate

Eye irritation: Severe - Rabbit

Sensitation: Not considered an occupational sensitizer

Ethylene glycol butyl ether 111-76-2

Oral ( LD 50): 917 mg/kg - Rat

Inhalation ( LC 50): 2900 mg/m<sup>3</sup>/7H - Rat

Skin irritation: Mild

Eye irritation: Mild

Sensitation: Not considered an occupational sensitizer

12

## ECOLOGICAL INFORMATION

On the basis of available information, this material is not expected to produce any significant environmental effects when recommended use instructions are followed.

13

## DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.

14

## TRANSPORT INFORMATION

Ship in accordance with 49 CFR parts 100-185. Non-hazardous for air, sea and road freight

## Power Burst

MSDS Number: S789

Revision Date: November 12, 2013

Page 5 of 5

### 15 REGULATORY INFORMATION

COMPONENT / (CAS/PERCENT) / CODES

- 
- \*Sodium Carbonate (497198 <19%) TSCA, WHMIS IDL
  - \*Sodium metasilicate (6834920 <8%) TSCA, WHMIS IDL
  - \*Sodium phosphate, tribasic (7601549 <6%) CERCLA, CSWHS, PA, TSCA
  - \*Ethylene Glycol Butyl Ether (111762 <4%) MASS, OSHAWAC, PA, TSCA, TXAIR, WHMIS IDL

REGULATORY KEY DESCRIPTIONS

-----

All components are listed on TSCA

CERCLA = Superfund clean up substance  
CSWHS = Clean water Act Hazardous substances  
MASS = MA Massachusetts Hazardous Substances List  
OSHA = OSHA workplace Air Contaminants  
PA = PA Right-To-Know List of Hazardous Substances  
TXAIR = TX Air Contaminants with Health Effects Screening Level  
WHMIS IDL = workforce Hazardous Material Information System Ingredient Disclosure List

### 16 OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager

Phone Number: [480] 899-7000