

SAFETY DATA SHEET

PRORESTORE.

PRODUCTS

Revision Date 20-May-2015
Version 1

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Crystal Odor Counteractant Professional Cherry
Product code LG-F1132

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Deodorizer
Restrictions on use Professional Use Only

1.3 Details of the supplier of the safety data sheet

Supplier Legend Brands
ProRestore Products
15180 Josh Wilson Road
Burlington, WA 98233
800-932-3030

1.4 Emergency telephone number

Emergency telephone number INFOTRAC 1-800-535-5053 (North America)
1-352-323-3500 (International)

2. Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910.1200

Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 1A

2.2 Label elements

Signal Word

Danger

Hazard Statements

Causes serious eye irritation
May cause an allergic skin reaction
May cause cancer



Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing should not be allowed out of the workplace

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3 Other Hazards Hazards not otherwise classified (HNOC)

Not Applicable

2.4 Other information

Not Applicable

Unknown Acute Toxicity

2.81841% of the mixture consists of ingredient(s) of unknown toxicity

3. Composition/Information on Ingredients

Substance

Chemical Name	CAS-No	Weight %
BENTONITE	1302-78-9	50 - 60
AMORPHOUS SILICA	7631-86-9	10 - 20
ALUMINUM OXIDE	1344-28-1	5 - 10
IRON OXIDE	1309-37-1	1 - 5
BENZALDEHYDE	100-52-7	1 - 5
CRYSTALLINE SILICA (QUARTZ)/ SILICA SAND	14808-60-7	1 - 5
CALCIUM OXIDE/LIME	1305-78-8	1 - 5
ISOPROPYL ALCOHOL	67-63-0	1 - 5
AMYL ACETATE	628-63-7	1 - 5
Ethyl Acetate	141-78-6	1 - 5
MAGNESIUM OXIDE	1309-48-4	< 1
TERPENES AND TERPENOIDS, SWEET ORANGE-OIL	68647-72-3	< 1
Benzyl acetate	140-11-4	< 1
Titanium dioxide	13463-67-7	< 1

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

4.1 Description of first-aid measures

General advice	No information available.
Eye contact	In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes. Call a poison control center or doctor for treatment advice. Tilt the head to prevent chemical from transferring to the uncontaminated eye.
Skin contact	Wash off immediately with soap and plenty of water. Remove all contaminated clothes and shoes.
Inhalation	Move to fresh air. Call a physician or poison control center immediately. If breathing is difficult, give oxygen. If not breathing, give artificial respiration.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Dilute with water or milk. Never give fluids if the victim is unconscious or having convulsions.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	See Section 2.2, Label Elements and/or Section 11, Toxicological effects.
-----------------	---

4.3 Recommendations for immediate medical care and/or special treatment

Notes to physician	Treat symptomatically.
---------------------------	------------------------

5. Fire-Fighting Measures

5.1 Extinguishing media

Suitable extinguishing media

Use CO₂, dry chemical, or foam. Water may be unsuitable for extinguishing fires. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

Unsuitable Extinguishing Media None.

5.2 Specific hazards arising from the substance or mixture

Special Hazard

None known based on information supplied

Hazardous Combustion Products No information available.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

5.3 Advice for firefighters

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. Thoroughly decontaminate all protective equipment after use. Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. .

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Dust Deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Nonsparking tools should be used.

Other information Follow personal protective equipment recommendations found in Section 8. Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow the spilled product to enter public drainage systems or open waterways. Do not allow smoking in the area.

6.2 Environmental precautions

See Section 12 for additional Ecological information.

6.3 Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. Handling and storage

7.1 Precautions for safe handling

Advice on safe handling Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.

Hygiene measures It is good practice to avoid contact with the product and/or its vapor, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

7.2 Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed. Store away from other materials. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals.

Materials to Avoid No materials to be especially mentioned.

8. Exposure controls/personal protection

8.1 Occupational Exposure Limits (OEL)

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWAEV
BENTONITE 1302-78-9	TWA: 1 mg/m ³ respirable fraction	-	TWA: 1.0 mg/m ³			TWA: 1 mg/m ³
AMORPHOUS SILICA 7631-86-9	-	TWA: 20 mppcf : (80)/(%) SiO ₂ mg/m ³ TWA				
ALUMINUM OXIDE 1344-28-1	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 1.0 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 1 mg/m ³
IRON OXIDE 1309-37-1	TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ TWA: 3 mg/m ³ TWA: 5 mg/m ³ STEL: 10 mg/m ³	TWA: 5 mg/m ³	TWA: 5 mg/m ³ TWA: 10 mg/m ³	TWA: 5 mg/m ³
BENZALDEHYDE 100-52-7	-	-				STEL: 4 ppm STEL: 17 mg/m ³
CRYSTALLINE SILICA (QUARTZ)/ SILICA SAND 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	: (30)/(%) SiO ₂ + 2 mg/m ³ TWA total dust : (250)/(%) SiO ₂ + 5) mppcf TWA	TWA: 0.025 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.10 mg/m ³

		respirable fraction : (10)/(%SiO2 + 2) mg/m ³ TWA respirable fraction				
CALCIUM OXIDE/LIME 1305-78-8	TWA: 2 mg/m ³	TWA: 5 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³	TWA: 2 mg/m ³
ISOPROPYL ALCOHOL 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm TWA: 492 mg/m ³ STEL: 400 ppm STEL: 984 mg/m ³	TWA: 400 ppm TWA: 985 mg/m ³ STEL: 500 ppm STEL: 1230 mg/m ³	TWA: 200 ppm STEL: 400 ppm
AMYL ACETATE 628-63-7	STEL: 100 ppm TWA: 50 ppm	TWA: 100 ppm TWA: 525 mg/m ³	TWA: 50 ppm STEL: 100 ppm	TWA: 50 ppm TWA: 266 mg/m ³ STEL: 100 ppm STEL: 532 mg/m ³	TWA: 50 ppm TWA: 266 mg/m ³ STEL: 100 ppm STEL: 532 mg/m ³	TWA: 50 ppm STEL: 100 ppm
Ethyl Acetate 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m ³	TWA: 150 ppm	TWA: 400 ppm TWA: 1440 mg/m ³	TWA: 400 ppm TWA: 1440 mg/m ³	TWA: 400 ppm
MAGNESIUM OXIDE 1309-48-4	TWA: 10 mg/m ³ inhalable fraction	TWA: 15 mg/m ³ fume, total particulate	TWA: 10 mg/m ³ TWA: 3 mg/m ³ STEL: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³
Benzyl acetate 140-11-4	TWA: 10 ppm	-	TWA: 10 ppm	TWA: 10 ppm TWA: 61 mg/m ³		TWA: 10 ppm
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³

8.2 Appropriate engineering controls

Engineering Measures

It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

8.3 Individual protection measures, such as personal protective equipment

Eye/Face Protection

Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to handling and processing of material.

Skin and body protection

Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.

Respiratory protection

If irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. NIOSH/MSHA approved respiratory protection should be worn if exposure is anticipated.

Hygiene measures

See section 7 for more information

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Solid
Appearance	crystalline
Color	Black and Beige
Odor	Cherry
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
pH		No information available
Melting/freezing point		No information available
Boiling point/boiling range		No information available
Flash Point		No information available
Evaporation rate		No information available
Flammability (solid, gas)		No information available
Flammability Limits in Air		
upper flammability limit		No information available
lower flammability limit		No information available
Vapor pressure		No information available
Vapor density		No information available
Specific Gravity	2.5	
Water solubility		No information available
Solubility in other solvents		No information available
Partition coefficient		No information available
Autoignition temperature		No information available
Decomposition temperature		No information available
Viscosity, kinematic		No information available
Viscosity, dynamic		No information available
Explosive properties		No information available
Oxidizing Properties		No information available

9.2 Other information

Volatile organic compounds (VOC) content 97.5 g/L

10. Stability and Reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under normal conditions

10.3 Possibility of hazardous reactions

None under normal processing.

10.4 Conditions to Avoid

Keep away from heat, sparks and flames.

10.5 Incompatible Materials

None known based on information supplied.

10.6 Hazardous Decomposition Products

Not determined.

11. Toxicological information

11.1 Acute toxicity

Numerical measures of toxicity: Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Unknown Acute Toxicity 2.81841% of the mixture consists of ingredient(s) of unknown toxicity

Oral LD50 7,356.00 mg/kg
Dermal LD50 10,529.00 mg/kg

Numerical measures of toxicity: Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
BENTONITE 1302-78-9	5000 mg/kg (Rat)	-	-
AMORPHOUS SILICA 7631-86-9	5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat) 1 h
ALUMINUM OXIDE 1344-28-1	5000 mg/kg (Rat)	-	-
IRON OXIDE 1309-37-1	10000 mg/kg (Rat)	-	-
BENZALDEHYDE 100-52-7	1292 mg/kg (Rat)	> 1250 mg/kg (Rabbit)	-
CRYSTALLINE SILICA (QUARTZ)/ SILICA SAND 14808-60-7	500 mg/kg (Rat)	-	-
CALCIUM OXIDE/LIME 1305-78-8	500 mg/kg (Rat)	-	-
ISOPROPYL ALCOHOL 67-63-0	1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
Ethyl Acetate 141-78-6	5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit)	-
TERPENES AND TERPENOIDS, SWEET ORANGE-OIL 68647-72-3	4400 mg/kg (Rat)	>5 g/kg (Rabbit)	-
Benzyl acetate 140-11-4	2490 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
Titanium dioxide 13463-67-7	10000 mg/kg (Rat)	-	-

11.2 Information on toxicological effects

Skin corrosion/irritation

Product Information

- No information available

Component Information

- No information available

Eye damage/irritation

Product Information

- No information available

Component Information

- No information available

Respiratory or skin sensitization

Product Information

- No information available

Component Information

- No information available

Germ Cell Mutagenicity

Product Information

• No information available

Component Information

• No information available

Carcinogenicity

• The table below indicates whether each agency has listed any ingredient as a carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
CRYSTALLINE SILICA (QUARTZ)/ SILICA SAND 14808-60-7	A2	Group 1	Known	
ISOPROPYL ALCOHOL 67-63-0	-	Group 1 Group 3	-	
Titanium dioxide 13463-67-7	-	Group 2B	-	

Reproductive toxicity

Product Information

• No information available

Component Information

• No information available

STOT - single exposure

No information available

STOT - repeated exposure

No information available

Other adverse effects

Target Organs

- Central nervous system
- Eyes
- Lungs
- Respiratory system
- Skin
- Not determined.

Product Information

• No information available

Component Information

• No information available

Aspiration hazard

Product Information

• No information available

Component Information

• No information available

12. Ecological information

12.1 Toxicity

Ecotoxicity

No information available

12.43122201 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Ecotoxicity effects

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
BENTONITE	-	LC50: 96 h Oncorhynchus mykiss	-

1302-78-9		19000 mg/L static	
AMORPHOUS SILICA 7631-86-9	EC50: 72 h Pseudokirchneriella subcapitata 440 mg/L	LC50: 96 h Brachydanio rerio 5000 mg/L static	EC50: 48 h Ceriodaphnia dubia 7600 mg/L
BENZALDEHYDE 100-52-7	-	LC50: 96 h Oncorhynchus mykiss 10.6 - 11.8 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 12.69 mg/L static LC50: 96 h Lepomis macrochirus 0.8 - 1.44 mg/L flow-through LC50: 96 h Pimephales promelas 6.8 - 8.53 mg/L flow-through LC50: 96 h Lepomis macrochirus 7.5 mg/L static	-
CALCIUM OXIDE/LIME 1305-78-8	-	LC50: 96 h Cyprinus carpio 1070 mg/L static	-
ISOPROPYL ALCOHOL 67-63-0	EC50: 96 h Desmodesmus subspicatus 1000 mg/L EC50: 72 h Desmodesmus subspicatus 1000 mg/L	LC50: 96 h Pimephales promelas 9640 mg/L flow-through LC50: 96 h Pimephales promelas 11130 mg/L static LC50: 96 h Lepomis macrochirus 1400000 µg/L	EC50: 48 h Daphnia magna 13299 mg/L
AMYL ACETATE 628-63-7	-	LC50: 96 h Lepomis macrochirus 650 mg/L static	-
Ethyl Acetate 141-78-6	-	LC50: 96 h Pimephales promelas 220 - 250 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 484 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 352 - 500 mg/L semi-static	EC50: 48 h Daphnia magna 560 mg/L Static

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

Discharge into the environment must be avoided

Chemical Name	log Pow
BENZALDEHYDE 100-52-7	1.48
ISOPROPYL ALCOHOL 67-63-0	0.05
Ethyl Acetate 141-78-6	0.6
Benzyl acetate 140-11-4	1.96

12.4 Mobility in soil

No information available.

12.5 Other adverse effects

No information available

13. Disposal Considerations

13.1 Waste Disposal Guidance

Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

14. Transport Information

DOT Not regulated

MEX	Not regulated
IMDG	Not regulated
IATA	Not regulated

15. Regulatory information

15.1 International Inventories

TSCA	Complies
DSL	Complies
EINECS/ELINCS	-
ENCS	-
IECSC	-
KECL	Complies
PICCS	-
AICS	-
NZIoC	-

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL - Canadian Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals

15.2 U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
ALUMINUM OXIDE 1344-28-1	1.0
ISOPROPYL ALCOHOL 67-63-0	1.0

15.3 Pesticide Information

Not applicable

15.4 U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
CRYSTALLINE SILICA (QUARTZ)/ SILICA SAND - 14808-60-7	Carcinogen
Titanium dioxide - 13463-67-7	Carcinogen
Estragole (Methyl chavicol) - 140-67-0	Carcinogen

16. Other information

NFPA	Health Hazard 1	Flammability 0	Instability 0	Physical and chemical hazards - Personal protection X
HMIS	Health Hazard 1	Flammability 0	Physical Hazard 0	

Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)
Ceiling (C)
DOT (Department of Transportation)
EPA (Environmental Protection Agency)
IARC (International Agency for Research on Cancer)
International Air Transport Association (IATA)
International Maritime Dangerous Goods (IMDG)
NIOSH (National Institute for Occupational Safety and Health)
NTP (National Toxicology Program)
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
PEL (Permissible Exposure Limit)
Reportable Quantity (RQ)
Skin designation (S*)
STEL (Short Term Exposure Limit)
TLV® (Threshold Limit Value)
TWA (time-weighted average)

Revision Date 20-May-2015

Revision Note

No information available

Disclaimer

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

End of Safety Data Sheet