

Ultracac Renovate

MSDS Number: A217

Revision Date: November 14, 2013

Page 1 of 5

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Kärcher North America, Inc.
Prochem
325 S. Price Road
Chandler, AZ 85224

Contact: Prochem
Phone: 480-899-7000
Fax: 480-786-9538
Email: info@prochem.com
Web: www.prochem.com

Product Name: Ultracac Renovate
Revision Date: November 14, 2013
Version: 45-100D
MSDS Number: A217


Emergency Information: INFOTRAC 1-800-535-5053 International 1-352-323-3500

2 HAZARDS IDENTIFICATION

Route of Entry: Eyes; Skin; Inhalation;
Target Organs: Eyes; Skin;
Inhalation: Minimal respiratory tract irritation may occur with exposure to a large amount of material.
Skin Contact: Causes irritation.
Eye Contact: Irritating to eyes; eye damage may occur.
Ingestion: Ingestion is not applicable route of entry for intended use.

NFPA:
HMIS III:

Health = 2, Fire = 1, Reactivity = 0
H2/F1/PH0



HMIS III	
HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARDS	0
PERSONAL PROTECTION B Safety Glasses, Gloves	

PERSONAL PROTECTION INDEX			
A		G	
B		H	
C		I	
D		J	
E		K	
F		X	Consult your supervisor or S.O.P. for "SPECIAL" handling directions
A	n	o	p
Safety Glasses	Splash Goggles	Face Shield & Eye Protection	Gloves
q	r	s	
Boots	Synthetic Apron	Full Suit	
t	u	w	y
Dust Respirator	Vapor Respirator	Dust & Vapor Respirator	Full Face Respirator
z			
Airline Hood or More			

Ultrapac Renovate

MSDS Number: A217

Revision Date: November 14, 2013

Page 2 of 5

GHS Hazard Pictograms:



GHS Classifications:

- Health, Acute toxicity, 5 Oral
- Health, Acute toxicity, 4 Dermal
- Health, Serious Eye Damage/Eye Irritation, 2 A

GHS Phrases:

- Warning, H303 - May be harmful if swallowed
- Warning, H312 - Harmful in contact with skin
- Warning, H319 - Causes serious eye irritation

GHS Precautionary Statements:

- Wash thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.
- IF ON SKIN: Wash with soap and water.
- IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
- Call a POISON CENTER or doctor/physician if you feel unwell.
- If eye irritation persists: Get medical advice/attention.
- Wash contaminated clothing before reuse.

3

HAZARDS IDENTIFICATION

Ingredients:

CAS #	Percentage	Chemical Name
1310-58-3	<2%	Potassium hydroxide, solution
102-71-6	<2%	Triethanolamine

OSHA Regulatory Status:

This SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

4

FIRST AID MEASURES

- Inhalation:** If symptoms develop, move victim to fresh air; if symptoms persist, obtain medical attention.
- Skin Contact:** Wash with soap and water. If irritation persists consult medical personnel.
- Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation. Get immediate medical attention.
- Ingestion:** If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. If injured party is conscious, give two glasses of water. Seek medical attention.

Ultrapac Renovate

MSDS Number: A217

Revision Date: November 14, 2013

Page 3 of 5

5 FIRE FIGHTING MEASURES

Flash Point: 100°C/ 212°F
Flash Point Method: Closed Cup

Wear self-contained breathing apparatus and other protective clothing. Use any standard agent - choose the one most appropriate for type of surrounding fire.

6 ACCIDENTAL RELEASE MEASURES

Keep away from drains and ground water. Keep all unnecessary personnel away. Spill area may be slippery. Pick up excess with inert absorbent material and place into separate waste container. Ventilate area and wash spill site after material pickup is complete. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

7 HANDLING AND STORAGE

Handling Precautions: Avoid contact with eyes, skin, or clothing; Consider normal working hygiene. Handle with care and avoid spillage on the floor (slippage). Keep away from sources of ignition; wash thoroughly after handling.
Storage Requirements: Keep away from children. Store in cool/dry area; Keep container closed.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Normal room ventilation is satisfactory for limited use.
Personal Protective Equip: HMIS PP, B | Safety glasses, Gloves

No OSHA PEL established for listed chemicals

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Opaque Yellow	Odor:	Citrus
Physical State:	Liquid	Solubility:	Soluble
Spec Grav./Density:	9.80 lb/gal		
pH:	12.98 as is / 10.5 - 11.5 RTU		

10 STABILITY AND REACTIVITY

Stability: Product is stable under normal conditions.
Conditions to Avoid: None known
Materials to Avoid: None known
Hazardous Decomposition: Exposure to fire may liberate carbon dioxide, carbon monoxide, organic acids, and other unidentified thermal decomposition products from this product or its packaging.
Hazardous Polymerization: Will not occur.

Ultrapac Renovate

MSDS Number: A217

Revision Date: November 14, 2013

Page 4 of 5

11 TOXICOLOGICAL INFORMATION

Toxicity Data:

Potassium hydroxide 1310-58-3

Oral (LD 50): 273 mg/kg - Rat

Inhalation (LC): Not listed on RTECS

Skin irritation: Severe - Human

Eye irritation: Severe - Rabbit

Sensitization: Not considered an occupational sensitizer

Triethanolamine 102-71-6

Oral (LD 50): 4920 mg/kg - Rat

Inhalation (LC): Not listed on RTECS

Skin irritation: Mild - Human

Eye irritation: Severe - Rabbit

Sensitization: Not considered an occupational sensitizer

12 ECOLOGICAL INFORMATION

On the basis of available information, this material is not expected to produce any significant environmental effects when recommended use instructions are followed.

13 DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.

14 TRANSPORT INFORMATION

Limited Quantity (Ltd Qty) Ship in accordance with 49 CFR parts 100-185.

Ultracac Renovate

MSDS Number: A217

Revision Date: November 14, 2013

Page 5 of 5

15 REGULATORY INFORMATION

COMPONENT / (CAS/PERCENT) / CODES

*Potassium hydroxide, solution (1310583 <2%) CERCLA, CSWS, MASS, OSHAWAC, PA, TSCA, TXAIR, WHMIS

*Triethanolamine (102716 <2%) HAP, MASS, PA, TSCA, TXAIR

REGULATORY KEY DESCRIPTIONS

All components are listed on TSCA

CERCLA = Superfund clean up substance

CSWS = Clean water Act Hazardous substances

HAP = Hazardous Air Pollutants

MASS = MA Massachusetts Hazardous Substances List

OSHA = OSHA workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

TXAIR = TX Air Contaminants with Health Effects Screening Level

WHMIS = workplace Haz Mat Info Sys Canada

16 OTHER INFORMATION

This document is prepared in accordance with 29 CFR 1910.1200. The purpose of this section is to ensure that the hazards of all chemicals produced or imported are evaluated, and that information concerning their hazards is transmitted to employers and employees.

All information appearing herein is based upon data obtained from the raw material manufacturer and/or recognized technical sources. While the information above is believed to be true and accurate, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the manufacturer's control; therefore the users are responsible to verify this data under their own particular conditions, applications and regulations to determine if the product is suitable for their particular purposes. The users assume all risks of product use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures or processes.

Prepared by: EHS Manager

Phone Number: [480] 899-7000