

## **SAFETY DATA SHEET**

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System.

THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)

IMPORTANT: Read this SDS before handling & disposing of this product.

Pass this information on to employees, customers, & users of this product.

### **SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER**

PRODUCT IDENTITY: STAIN ZONE  
PRODUCT PURPOSE: SPOTTER  
COMPANY IDENTITY: Bridgepoint Systems  
COMPANY ADDRESS: 4282 S 590 W  
COMPANY CITY: Salt Lake City, UT 84123  
COMPANY PHONE: 1-800-658-5314  
EMERGENCY PHONES: INFOTRAC: 1-800-535-5053 (USA)



### **SECTION 2. HAZARDS IDENTIFICATION**

#### **WARNING**

**EXPOSURE PREVENTION: AVOID EXPOSURE OF ADOLESCENTS, CHILDREN!**

#### **HAZARD STATEMENTS:**

**H100s = General, H200s = Physical, H300s = Health, H400s = Environmental**

H270 May cause or intensify fire; Oxidizer.  
H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H320 Causes eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.

#### **PRECAUTIONARY STATEMENTS:**

**P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal**

P210 Keep away from heat/sparks/open flames/hot surfaces - No smoking.  
P262 Do not get in eyes, on skin, or on clothing.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present & easy to do - Continue rinsing.  
P404 Store in a closed container.

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

<b>MATERIAL</b>	<b>CAS#</b>	<b>EINECS#</b>	<b>WT %</b>
Hydrogen Peroxide	7722-84-1	231-765-0	< 8
2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	0-10
2-Butoxyethanol	111-76-2	203-905-0	0- 5

TRACE COMPONENTS: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

**SEE SECTIONS 8, 11 & 12 FOR TOXICOLOGICAL INFORMATION.**

### **SECTION 4. FIRST AID MEASURES**

#### **EYE CONTACT:**

For eyes, flush with plenty of water for 15 minutes & get medical attention.

#### **SKIN CONTACT:**

In case of contact with skin immediately remove contaminated clothing.  
Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

COMPANY IDENTITY: Bridgepoint Systems  
PRODUCT IDENTITY: STAIN ZONE

SDS DATE: 09/29/2016  
REPLACES: 09/10/2013

**SECTION 4. FIRST AID MEASURES (CONTINUED)**

**INHALATION:**

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR).  
CALL A PHYSICIAN immediately!

**SWALLOWING:**

Rinse mouth. Give plenty of water to drink. Do NOT induce vomiting.  
GET MEDICAL ATTENTION IMMEDIATELY. Do NOT give liquids to an unconscious or convulsing person.

**SECTION 5. FIRE FIGHTING MEASURES**

**FIRE & EXPLOSION PREVENTIVE MEASURES**

NO open flames. NO contact with oxidants. Above flash point, use a closed system, ventilation, explosion-proof electrical equipment, lighting. Do NOT use compressed air for filling, discharging, or handling.

**EXTINGUISHING MEDIA**

Use dry powder, alcohol-resistant foam, water spray, water in large amounts, carbon dioxide.

**SPECIAL FIRE FIGHTING PROCEDURES**

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots). Use NIOSH approved positive-pressure self-contained breathing apparatus.

**UNUSUAL EXPLOSION AND FIRE PROCEDURES**

**OXIDIZER!!**

Reacts with most metals producing hydrogen which is extremely flammable & may explode. Applying to hot surfaces requires special precautions. Closed containers may explode if exposed to extreme heat. Isolate from oxidizers, reducers, organics, reactive metals, extreme heat, & open flame. Applying to hot surfaces requires special precautions. Continue all label precautions!

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

**PERSONAL PROTECTIVE MEASURES:**

EVACUATE DANGER AREA! Consult an expert! Keep unprotected personnel away. Use complete chemical protective suit with self-contained breathing apparatus.

**ENVIRONMENTAL PRECAUTIONS:**

Keep from entering storm sewers and ditches which lead to waterways.

**CONTAINMENT AND CLEAN-UP MEASURES:**

Stop spill at source. Dike and contain. Collect leaking liquid in sealable containers. Absorb remaining liquid in sand or inert absorbent.

**SECTION 7. HANDLING AND STORAGE**

**HANDLING**

Isolate from oxidizers, heat, & open flame. Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Do not get in eyes, on skin or clothing. Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse. Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, braze, or weld. Continue all label precautions!

COMPANY IDENTITY: Bridgepoint Systems  
 PRODUCT IDENTITY: STAIN ZONE

SDS DATE: 09/29/2016  
 REPLACES: 09/10/2013

## SECTION 7. HANDLING AND STORAGE (CONTINUED)

### STORAGE

Keep in fireproof surroundings. Keep separated from strong oxidants, food & feedstuffs.  
 Keep cool. Do not store above 49 C/120 F.  
 Keep container tightly closed & upright when not in use to prevent leakage.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

MATERIAL	CAS#	EINECS#	TWA (OSHA)	TLV (ACGIH)
Hydrogen Peroxide	7722-84-1	231-765-0	1 ppm	1 ppm
2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	None Known	25 ppm
2-Butoxyethanol	111-76-2	203-905-0	50 ppm S	20 ppm

MATERIAL	CAS#	EINECS#	CEILING	STEL (OSHA/ACGIH)	HAP
2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	None Known	None Known	Yes

Each component showing 'Yes' under "HAP" is an EPA Hazardous Air Pollutant.

### RESPIRATORY EXPOSURE CONTROLS

A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z86.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

### VENTILATION

LOCAL EXHAUST: Necessary                      MECHANICAL (GENERAL): Acceptable  
 SPECIAL: None                                      OTHER: None  
 Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

### EYE PROTECTION:

Splash goggles or safety glasses. Face-shields are recommended when the operation can generate splashes, sprays or mists.

### HAND PROTECTION:

Wear appropriate impervious gloves for routine industrial use. Use impervious gloves for spill response, as stated in Section 6 of this SDS (Accidental Release Measures).

NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

### BODY PROTECTION:

Use body protection appropriate for task.

## SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE:	Clear Liquid
ODOR:	Peroxide Solvent
ODOR THRESHOLD:	Not Available
pH (Neutrality):	5.0
MELTING POINT/FREEZING POINT:	Not Available
BOILING RANGE (IBP,50%,Dry Point):	> 105 C / > 222 F
FLASH POINT (TEST METHOD):	> 100 C / > 212 F
EVAPORATION RATE (n-BUTYL ACETATE=1):	Not Applicable
FLAMMABILITY CLASSIFICATION:	Class IIIB
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	0.95 (Lowest Component)
UPPER FLAMMABLE LIMIT IN AIR (% by vol):	Not Available
VAPOR PRESSURE (mm of Hg)@20 C	17.4
VAPOR DENSITY (air=1):	0.866

COMPANY IDENTITY: Bridgepoint Systems  
 PRODUCT IDENTITY: STAIN ZONE

SDS DATE: 09/29/2016  
 REPLACES: 09/10/2013

### **SECTION 9. PHYSICAL & CHEMICAL PROPERTIES (CONTINUED)**

GRAVITY @ 68/68 F / 20/20 C:	
DENSITY:	1.040
SPECIFIC GRAVITY (Water=1):	1.041
POUNDS/GALLON:	8.671
WATER SOLUBILITY:	Complete
PARTITION COEFFICIENT (n-Octane/Water):	Not Available
AUTO IGNITION TEMPERATURE:	398 C / 750 F
DECOMPOSITION TEMPERATURE:	Not Available
VOCs (>0.044 Lbs/Sq In) :	Not Available
TOTAL VOC'S (TVOC)*:	0.08 Lbs/Gal
NONEXEMPT VOC'S (CVOC)*:	0.08 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS):	6.3 Wt%
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C)	Not Available
VISCOSITY @ 20 C (ASTM D445):	Not Available

\* Using CARB (California Air Resources Board Rules).

### **SECTION 10. STABILITY & REACTIVITY**

#### STABILITY

Stable under normal conditions.

#### CONDITIONS TO AVOID

Isolate from extreme heat, & open flame.

#### MATERIALS TO AVOID

Reacts violently with organics, reactive metals, and reducers, causing fire & explosion hazard.

#### HAZARDOUS DECOMPOSITION PRODUCTS

Carbon Monoxide, Carbon Dioxide from burning.

#### HAZARDOUS POLYMERIZATION

Will not occur.

### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **ACUTE HAZARDS**

#### EYE & SKIN CONTACT:

Primary irritation to skin, defatting, dermatitis.  
 Absorption thru skin increases exposure.  
 Primary irritation to eyes, redness, tearing, blurred vision.  
 Liquid can cause eye irritation. Wash thoroughly after handling.

#### INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.

#### SWALLOWING:

Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

#### **SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED**

#### CONDITIONS AGGRAVATED

Persons with severe skin, liver or kidney problems should avoid use.

#### **CHRONIC HAZARDS**

#### CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:

This product has no carcinogens listed by IARC, NTP, NIOSH, OSHA or ACGIH, as of this date, greater or equal to 0.1%.

Absorption thru skin may be harmful.

Depending on degree of exposure, periodic medical examination is indicated.

COMPANY IDENTITY: Bridgepoint Systems  
 PRODUCT IDENTITY: STAIN ZONE

SDS DATE: 09/29/2016  
 REPLACES: 09/10/2013

### **SECTION 11. TOXICOLOGICAL INFORMATION**

IRRITANCY OF PRODUCT: This product is irritating to contaminated tissue.

SENSITIZATION TO THE PRODUCT: No component of this product is known to be a sensitizer.

MUTAGENICITY: This product is not reported to produce mutagenic effects in humans.

EMBRYOTOXICITY: This product is not reported to produce embryotoxic effects in humans.

TERATOGENICITY: This product is not reported to produce teratogenic effects in humans.

REPRODUCTIVE TOXICITY: This product is not reported to cause reproductive effects in humans.

A mutagen is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An embryotoxin is a chemical which causes damage to a developing embryo (such as: within the eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A teratogen is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A reproductive toxin is any substance which interferes in any way with the reproductive process.

### **MAMMALIAN TOXICITY INFORMATION**

<b>MATERIAL</b>	<b>CAS#</b>	<b>EINECS#</b>	<b>LOWEST KNOWN LETHAL DOSE DATA</b>
Diethylene Glycol Butyl Ether	112-34-5	203-961-6	LOWEST KNOWN LD50 (ORAL) 6560.0 mg/kg(Rats)
Diethylene Glycol Butyl Ether	112-34-5	203-961-6	LOWEST KNOWN LD50 (SKIN) 4120.0 mg/kg (Rabbits)

### **SECTION 12. ECOLOGICAL INFORMATION**

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

#### **EFFECT OF MATERIAL ON PLANTS AND ANIMALS:**

This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's components on test animals.

#### **EFFECT OF MATERIAL ON AQUATIC LIFE:**

The most sensitive known aquatic group to any component of this product is: Goldfish 250 ppm or mg/L (24 hour exposure).  
 Keep out of sewers and natural water supplies.

#### **MOBILITY IN SOIL**

This material is a mobile liquid.

#### **DEGRADABILITY**

This product is completely biodegradable.

#### **ACCUMULATION**

Bioaccumulation of this product has not been determined.

### **SECTION 13. DISPOSAL CONSIDERATIONS**

Processing, use or contamination may change the waste disposal requirements. Do not dispose of on land, in surface waters, or in storm drains. Waste should be recycled or disposed of in accordance with regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal.

**ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES. EPA CHARACTERISTIC: D002**

COMPANY IDENTITY: Bridgepoint Systems  
 PRODUCT IDENTITY: STAIN ZONE

SDS DATE: 09/29/2016  
 REPLACES: 09/10/2013

**SECTION 14. TRANSPORT INFORMATION**


OT/TDG SHIP NAME: Not Regulated  
 DRUM LABEL: None  
 IATA / ICAO: NOT RECOMMENDED FOR SHIPMENT BY AIR  
 IMO / IMDG: Not Regulated  
 EMERGENCY RESPONSE GUIDEBOOK NUMBER: None

**Air Transportation:** With a vented seal/cap, this item cannot be shipped via air in accordance with CFR49 173-24(g).

**SECTION 15. REGULATORY INFORMATION**

EPA REGULATION:  
 SARA SECTION 311/312 HAZARDS: Acute Health, Chronic Health, Reactive

All components of this product are on the TSCA list.  
 SARA Title III Section 313 Supplier Notification  
 This product contains the indicated <\*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.



SARA TITLE III INGREDIENTS	CAS#	EINECS#	WT%	(REG. SECTION)	RQ(LBS)
*2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	0-10	(313)	None
*2-Butoxyethanol	111-76-2	203-905-0	0- 5	(313)	None

Any release equal to or exceeding the RQ must be reported to the National Response Center (800-424-8802) and appropriate state and local regulatory agencies as described in 40 CFR 302.6 and 40 CFR 355.40 respectively. Failure to report may result in substantial civil and criminal penalties. State & local regulations may be more restrictive than federal regulations.

STATE REGULATIONS:  
 CALIFORNIA SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT (PROPOSITION 65):  
 This product contains no chemicals known to the State of California to cause cancer or reproductive toxicity.

INTERNATIONAL REGULATIONS  
 The components of this product are listed on the chemical inventories of the following countries:  
 Australia (AICS), Canada (DSL or NDSL), China (IECSC), Europe (EINECS, ELINCS)G  
 Japan (METI/CSCL, MHLW/ISHL), South Korea (KECI), New Zealand (NZIoC),  
 Philippines (PICCS), Switzerland (SWISS), Taiwan (NECSI), USA (TSCA).

CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)  
 C: Oxidizing Material.  
 D2B: Irritating to skin / eyes.

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

COMPANY IDENTITY: Bridgepoint Systems  
PRODUCT IDENTITY: STAIN ZONE

SDS DATE: 09/29/2016  
REPLACES: 09/10/2013

**SECTION 16. OTHER INFORMATION**

**HAZARD RATINGS:**

HEALTH (NFPA): 2, HEALTH (HMIS): 2, FLAMMABILITY: 1, PHYSICAL HAZARD: 1  
(Personal Protection Rating to be supplied by user based on use conditions.)  
This information is intended solely for the use of individuals  
trained in the NFPA & HMIS hazard rating systems.

**EMPLOYEE TRAINING**

See Section 2 for Risk & Safety Statements. Employees should be made aware  
of all hazards of this material (as stated in this SDS) before handling it.

SDS DATE: 09/29/2016

**NOTICE**

Bridgepoint Systems disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.